			Hazelhatch to Park West					
_			Hazelhatch to Park West					
		Requirement			-New track configuration SSFF, with two Slow Tracks on the North -Electrification of DART+ tracks -Provide access to DART platforms from Slow lines -Track alignment and drainage requirements (standards)			
					Intervention	Assessment		
	Baseline intervention (not subject to options)			-	-	-		
	Option 0: Do Nothing	Engineering	Feasibility	Constructability Geometrical fitness for intervention Safety	Leave as is	•		
				New track configuration SSFF, with two Slow Tracks on the North			Fail	Will not provide direct link between DART lines and platforms
			Requirements	Electrification of DART+ tracks Provide access to DART platforms from Slow lines				pations
1)				Track alignment and drainage (standards)				
Options Level 1 (PC 1)		Economy Environment		Investment guidelines and programme for DART+				
	Option 1: Do Minimum	Engineering	Feasibility	Constructability Geometrical fitness for intervention	n Install P&Cs and required track re-arrangement to provide access to new DART Platforms. Electrification of DART+ tracks S	0		
				Safety New track configuration SSFF, with two Slow Tracks on the North		•	Pass	
			Requirements	Electrification of DART+ tracks Provide access to DART platforms from Slow lines				
				Track alignment and drainage (standards)				
		Economy Environment		Investment guidelines and programme for DART+				